

6 ft. Garden Aviary Assembly Instructions And Parts List

Parts:

7	Side Panels
1	Door Panel
8	Pie Section Roof Panels
1	6' Roof Support Bar
2	Roof Support Bar Tabs
1	6' Stabilizing Bar
1	Metal Roof Cap
1	Metal Roof Support Plate

Screws and Nuts:

8	Roof Perimeter Screws
8	Stabilizing/Roof Support Bar Screws
1	Metal Roof Support Plate Screw
1	Long Screw for Center Roof Securing
1	Fender Washer
1	Lock Nut
1	Allen wrench for socket head screws

Instructions:

NOTE: It is important not to force the bolt more than one-half turn at a time when pre-tapping nut threads. If more turns are needed, insert a new screw and turn another half turn. Repeat until threads are clear. It is best to have a tapping tool on hand if needed. The correct size is Metric # 6.

1. Stand door panel in upright position.
2. Next, attach a wire panel to the door by placing its male hinges into female hinges on door panel. This will be to the right of door panel if facing door panel from the inside.
3. Working clockwise attach all remaining panels one at a time in the same manner.
4. Attach roof support bar tabs to each end of angled roof support bar using the small screws.
5. Attach metal roof support plate (the smaller one) to the pinnacle of the angled roof support beam using one small screw.
6. Attach the angled roof support beam to any two opposing panels by screwing the tabs on the beam to the two screw receptors on the inside of the top horizontal tubing of the panels using the short screws.
7. In the same manner, attach the straight stabilizing bar to two opposing panels so that both beams are perpendicular to one another.
8. Attach a roof section to the outside of the top horizontal tube frame of any panel by using one of the short screws. Note: The tip of the roof panel should simply lie on top of the metal roof support plate that is attached to the angled roof support bar. Someone will need to be inside on a step ladder to hold the roof tips stable during remaining roof assembly.
9. Working counter clock-wise, slide each pie shaped roof section onto the previously placed roof section using the groove of each section as a guide. Note: Do not tighten screws just yet. Some adjustment may be needed when placing the final roof section into place. Slightly pushing on various corners of the aviary will adjust the geometric shape of the octagon and will allow for the correct placement of the roof sections.
10. Place metal roof cap on top of roof pinnacle and secure the entire roof assembly using the long screw, fender washer, and lock nut.

Note:

Our Powder Coat colors have been coordinated with Rust-O-Leum Gloss Enamel. It is available at most any local hardware or home improvement store. It is non toxic, and provides a tough enamel finish for you to use as convenient touch up as needed.